

→ Automatic volumetric Low consumption.


VD BLACK 10

(Ref. 960472)

TECHNICAL SPECIFICATIONS

MODEL	VD BLACK 10
CODE	960472
RESIN VOLUME	10
WORK FLOW RATE	1 m ³ /h
LOW CAPACITY CONFIGURATION	
SALT / REGENERATION	0,6 kg salt
EXCHANGE CAPACITY	31,5°HFxm ³
MEDIUM CAPACITY CONFIGURATION	
SALT / REGENERATION	1 kg salt
EXCHANGE CAPACITY	46,2°HFxm ³
HIGH CAPACITY CONFIGURATION	
SALT / REGENERATION	2,1 kg salt
EXCHANGE CAPACITY	57°HFxm ³
TEMPERATURE RANGE	4-43°C
PRESSURE RANGE	2,5-8 bar
PRESSURE CLASSIFICATION	
ELECTRIC CONNECTION	220V/ 50Hz -12VAC
NOMINAL ELECTRICAL POWER	4W

-  ELECTRONIC PROGRAMMER
-  MIXING VALVE
-  INTEGRATED BY-PASS
-  MULTILINGUAL PROGRAMMER
ESP
FRA
ENG



CERTIFIED
UNE 149101
EQUIPMENT

MEMBER
 **Water
Quality
ASSOCIATION**

WLG (B-60326279), is member of the Water Quality Association.



ACREDITED BY ENAC
Certif. nº 34/5200/14/0712

The trading of water treatment and household appliances as well as designing and teaching of non-official training courses related with its technology are certified and comply with the UNE-ISO-9001 far WLG (B-60326279).



WLG (B-60326279) is an Aqua España member, who belongs Aqua Europa (Federation of European nation associations).



WLG (B-60326279), has the rights granted for Authorized Economic Operator with number ESAEOF18000008U6 and 13/02/2018 as a date of entry of the authorization.